

DC INVERTER MMA WELDING MACHINES



FEATURES

- Small in size, light weight and easy to carry.
- Good performance with automatic compensation for voltage fluctuation.
- Low open energy wastage, energy saving.
- Suitable for welding of stainless steel and mild steel products.

TECHNICAL PARAMETER

MODEL		IA2000	IA2500	MA3000	IA5000
Input Voltage	V	1PH 240V 50/60Hz	1PH 240V 50/60Hz	3PH 415V 50/60Hz	3PH 415V 50/60Hz
Rated Input Power Capacity	KVA	5.3	10.4	9.4	21
No - Load Voltage	V	67	68	54	75
Output Current Range	A	20-200	20-230	20-300	20-500
Rated Output Voltage	V	26.4	28	30	32
Duty Cycle	%	60	60	60	60
Electrode Diameter	mm	1.6-3.2	1.6-4.0	1.6-4.0	1.6-5.0
Efficiency	%	85	85	85	85
Power Factor	Cos ϕ	0.76	0.76	0.93	0.93
Insulation Class		F	F	F	F
Gross Weight	KG	5.3	8.5	19	20
Dimension	mm	315 x 115 x 197	370 x 150 x 240	480 x 205 x 322	470 x 260 x 465
Protection Class		IP23	IP23	IP23	IP23

SERVICE CENTER

TTMC WELDING SUPPLIES SDN BHD

No.3, Jalan PTP 1/4,
Taman Perindustrian Tasik Perdana,
47120 Puchong, Selangor, Malaysia.
Tel : 03-8060 6131 Fax : 03-8060 6639
Email: derrick@ttmcwelding.com

TTMC SDN BHD

No.3, Jalan Perdagangan 11,
Taman Universiti Industrial Park,
81300 Skudai, Johor, Malaysia.
Tel : 07-520 2093 Fax : 07-520 2016
Email: ttmclim@ttmcwelding.com

Branch

No.21, Jalan Mutiara Emas 7/7,
Taman Mount Austin,
81100 Johor Bahru, Johor, Malaysia.