

DC INVERTER HF TIG WELDER & AC/DC INVERTER HF TIG WELDER



FEATURES

- Light weight, portable DC, AC/DC TIG .
- Reliable and proven control circuit design with wide range of weld current control .
- AC/DC output pulse function, high frequency arc start with excellent penetration weld.
- Layers to protection circuit are built in for safety and reliability.
- Suitable for sheet metal welding of steel , stainless steel for kitchen equipment, ornamental steel and various other industries.

TECHNICAL PARAMETER

MODEL		TIG-250M	TIG-200ACDC	TIG-315ACDC
Input Voltage	V	1PH 240V 50/60Hz	1PH 240V 50/60Hz	3PH 415V 50/60Hz
Rated Input Power Capacity	KVA	8.3	4.5	8.9
No - Load voltage	V	65	56	54
Output Current Range	A	20-250	20-200	10-315
Rated Output Voltage	V	10.4-20	10.4-18	-
Duty Cycle	%	60	60	60
Efficiency	%	85	85	High HF
Power Factor	Cos ϕ	0.93	0.93	0.93
Insulation Class		F	F	F
Protection Class		IP21	IP21	IP21
Gross Weight	KG	19	20	36
Dimension	MM	410 x 200 x 280	493 x 330 x 320	615 x 256 x 523

SERVICE CENTER

TTMC WELDING SUPPLIES SDN BHD

No.3, Jalan PTP 1/4,
Taman Perindustrian Tasik Perdana,
47120 Puchong, Selangor, Malaysia.
Tel : 03-8060 6131 Fax : 03-8060 6639
Email: derrick@ttmcwelding.com

TTMC SDN BHD

No.3, Jalan Perdagangan 11,
Taman Universiti Industrial Park,
81300 Skudai, Johor, Malaysia.
Tel : 07-5202093 Fax : 07-5202016
Email: ttmclim@ttmcwelding.com

Branch

No.21, Jalan Mutiara Emas 7/7,
Taman Mount Austin,
81100 Johor Bahru, Johor, Malaysia.